

ACCESS PANELS

General Product Specification

Features:

- Choice of 5 ergonomic sizes
- Thermal, Acoustic and Fire retardant insulation
- Double Skin, Sandwich Construction lift off doors
- Simple Progressive Camlock Fastening
- Positive Seal Gasket
- Pre-punched Flange holes for easy installation
- Safety retaining chain as standard
- Oval Shape for easy Cut-Out, template provided with each carton
- Suitable for Plain and Insulated Ducting

Approvals:

- Conformance to D.W. 142 Class A,B & C
- Conformance to Eurovent classes as above
- Quality Assured BS5750 Pt 2
- Shock tested to DEF Std 07-55

Reference Dimensions:

The following dimensions are for use as a general guide. A cutting template is included in each carton.



Ergonomic Sizing:

The standard duct access door sizes have been selected after careful study of the needs of site engineering and maintenance personnel. Each door allows a different degree of access, enabling the most appropriate unit to be specified, depending on the type of equipment installed in the ducting, and the likely maintenance needs.

Order Code	Size		No. Per Carton	Weight Per Carton Kg	Volume Per Carton m ³
	mm	Inches			
AP-00	200 x 125	8 x 5	20	11	.042
AP-10	300 x 150	12 x 6	10	9	.034
AP-20	460 x 250	18 x 10	10	19	.072
AP-30	530 x 360	21 x 14	5	16	.084
AP-40	635 x 430	25 x 17	4	17	.064

AP-00
Hand/Sight



AP-10
One Hand & Sight



AP-20
Two Hands & Sight



AP-30
Head & Shoulders



AP-40
Body Entry & Ladder

