ACCESS PANELS

SMOOTHFLO PRODUCTS PTY LTD
For more information visit www.smoothflo.com.au

General Product Specification

Features:
- Choice of 4 ergonomic sizes
- Thermal, Acoustic and Fire retardant insulation
- Double Skin, Sandwich Construction lift off doors
- Simple Progressive Camlock Fastening
- Positive Seal Gasket
- Pre-punched Flange holes for easy installation
- Safety retaining chain as standard
- Oval Shape for easy Cut-Out, template provided with each carton
- Suitable for Plain and Insulated Ducting

Approvals:
- Conformance to D.W. 142 Class A,B & C
- Conformance to Eurovent classes as above
- Quality Assured BS5750 Pt 2
- Shock tested to DEF Std 07-55

Reference Dimensions:
The following dimensions are for use as a general guide. A cutting template is included in each carton.



Ergonomic Sizing:
The standard duct access door sizes have been selected after careful study of the needs of site engineering and maintenance personnel. Each door allows a different degree of access, enabling the most appropriate unit to be specified, depending on the type of equipment installed in the ducting, and the likely maintenance needs.

Order Code	Size mm	No. Per Carton	Weight Per Carton Kg
AP1 - R	250 x 150	10	11
AP2 - R	380 x 250	10	9
AP3 -R	510 x 380	5	19
AP4 - R	660 x 510	3	16